

FOREMOST APEX 65

TOP DRIVE

Stroke 25 ft (7.6 m)

Pullback: 65,000 lbs (29,484kg) **Hoist Capacity** 22,000 lbs (9,979 kg) Pulldown:

150 ft/min (46 m/min) **Hoist Speed** 22,000 ft-lbs (29828 Nm) Torque (stall)

Low Speed: 12.000 ft-lbs (16.270 N-m) @ 110 RPM **Rotation Speed** High Speed: 8,200 ft-lbs (11,118 N-m) @ 165 RPM

4-1/2" (114 mm) **Spindle Thru Hole**

Tilting Capacity 1,500 lbs (680 kg) @ 70 degrees

COMPRESSOR

Air Flow 1250 cfm Pressure 350 psi

Plumbing 1,000 psi rated

Engine Power 675 HP (tier 3 or tier 4)

TABLE

14" (356 mm)

Hands Free Breakout 4" - 8-5/8" (102 mm - 219 mm) OD Pipe

SERVICE WINCH

Wire Rope Length 140 ft (42.7 m) **Wire Rope Diamter** ½" (13 mm)

Line Pull on Bare Drum 6,000 lbs (2,722 kg) **Line Speed on Full Drum** 100 ft/min (30 m/min)

WATER AND FOAM INJECTION


Capacity 24 gpm **Pressure** 700 psi


DIMENSIONS

Tracked: 40' 1" (12.2 m) Length Chassis: 41' 1" (12.5 m) Tracked: 13' 4" (4.1 m) Height Chassis: 13' 5" (4.1 m) Tracked: 10' 5" (3.2 m) Width Chassis: 8' 6" (2.6 m)

Tracked: 72,600 lbs (32,930 kg) Weight Chassis: 70,610 lbs (32,020 kg)







OPTIONS

Carrier Tracks, chassis, or deck kit

Power: 675 HP **Engine** Emissions: Tier 3 (Stage IIIa) or Tier 4 (Stage IV)

1000/500 Compressor

Pipehandling Foremost hands free pipehandling system

Sampling cyclone, sandline winch, hose minder winch, special request **Misc. Options** water pump, side mounted breakout for casing/hammers/bits, data acquisition, cold weather package, fire suppression system.

FEATURES

- Vertical to 45 degrees angle drilling
- Cylinder driven gear feed system
- Hydraulically operated split table
- Remote driller's console
- Mast base rotation barrier
- Blowdown valve
- Electric over hydraulic controls
- Bellybox controls for set up and pipehandling
- Hydraulic split deck (tracked configuration) 0-25 degrees



