

MR3003C

Vibration & Motion Measurement System



The MR3003C in SYSCOM's rugged RED BOX is a compact vibration/motion measurement system. As such it meets all user expectation in a state-of-the-art device and thus is a highly reliable and efficient tool for many applications. It is suitable for structural monitoring and for human comfort evaluations based on VDV - Vibration Dose Values and RMS values.

Applications

- **Civil Engineering and Human comfort**
Industrial Vibrations - Construction Site Monitoring - Tunneling
- Truck and Rail Traffic - Blasting Monitoring - Model Verification
- **Earthquake Engineering**
Building Monitoring - Monitoring of Structures (Dams, Bridges..)
- **Geology**
Soil Characterization
- **Earth Science**
Earthquake Monitoring (seismic Intensity)
Continuous data stream in MiniSeed/SeedLink format

MR3003C Vibration & Motion Measurement System

The MR3003C in SYSCOM's rugged RED BOX is a compact vibration/motion measurement system. As such it meets all user expectation in a state-of-the-art device and thus is a highly reliable and efficient tool for many applications. The MR3003C is suitable for structural monitoring (DIN 4150-3, SN 640312 and others) and human comfort (DIN 4150-2, ISO 2631 and others).

Major features

- Compact unit containing sensor, digital recorder and communication
- Dual core ARM processor
- Internal 4G modem, fallback 3G/2G
- Internal 4GB memory
- Embedded Web Server for easy configuration and control
- Precise timing (GPS)
- Power over Ethernet (PoE)
- Wide dynamic range
- Wireless connectivity



MR3003C with 4G module and mounting plate, lateral view.

Data acquisition

Resolution	24 bits
Sampling-rate	250, 500, 1'000, 2'000, 4'000 sps
Number of channels	3
Channel to channel skew	None – simultaneous sampling on all channels
Dynamic range	Typ. 130dB@250 sps, 124dB@1000 sps
Data Filter	FIR & IIR digital filters
Trigger Filter	Digital IIR filter: 0.5 - 15 Hz band-pass (only for accelerometer)

Trigger and de-trigger

Principle	Level trigger or STA/LTA
Trigger voting logic	Predefined AND or OR combinations, individual channel votes
Level trigger	0.003 to 100% full scale
STA / LTA (for acceler.)	STA: 0,1 to 25s, LTA: 1 to 250s, Ratio: 0,1 to 25.
Smart Trigger / De-Trigger	Automatic adjustment of trigger level

Microprocessor

Recording principle	Event recording (time history), continuous time recording, manually triggered or timed recording
Header	Contains status information at time of trigger and event summary
Pre-event recording	1-99 seconds (@250Hz), others depending on sampling rate
Post-event recording	1-100 seconds
Data memory	Removable SD card (4Gb)
Alarm triggers	
Principle	Two alarm levels independently settable as: threshold levels, curves defined by the main standards or user-defined curves
Alarm level range	0.1 % to 100% full scale
Alarm based on standards	Different built-in standards: DIN 4150-3 (Germany), SN 640312 (Switzerland), Circulaire du 23/07/1986 (France), Önorm S 9020 (Austria)
User-defined alarm	Thresholds and frequencies individually settable for each axis
Notifications	Various notification options, individually settable for each axis
Precision timing	
System Clock	1 ppm, this clock is disciplined by GPS, NTP
Data/user interface	
Intelligent Alerting	System initiates communications or sends text message (SMS) or e-mail when an event is detected
Web Interface	Easy to use command & control through embedded web server
FTP	Built-in client protocol supporting FTP, SFTP, FTPS able to push to a server

Display

3 LED	Run, Recording, Warning/Error
LCD-Display	Status information, important settings, event-related information

Wireless Communication

WiFi	IEEE 802.11 b/g/n compliant
Mobile Network (option)	Internal 4G modem, fallback 3G/2G

Power Supply

Supply Voltage	9 - 14.5VDC or 48V PoE
Power Consumption	From 1 W to 1.4 W depending on the configuration (velocitymeter) From 1.3 W to 1.7 W depending on the configuration (accelerometer)

I/O and Connectors

Type	Metallic self-latching push-pull connectors with positioning key (LEMO)
Power	Metallic connector with protective GND
GPS	Connector for external GPS
LAN / PoE	Communication with PC or network - Ethernet 100BaseT

Sensors (Internal)

Triaxial Velocitymeter Type

Velocity sensor with linearized frequency response
A3HV 315/1 (triaxial) (according to DIN 45669)

Principle

Geophone

Measuring range full scale

± 100 mm/s

Frequency range

1 - 350 Hz

Case-to-coil motion

4 mm p-p

Dynamic range

> 130 dB

Linearity/Phase

According to DIN 45669 (class 1)

Cross axis sensitivity

According to DIN 45669 (<5%)

Orientation

Horizontal (floor) mounting or vertical (wall mounting)

Triaxial Accelerometer

Principle

The MEMS accelerometer consists in a micro-machined capacitive sensing element (MEMS) and a custom low-power mixed-signal integrated circuit (ASIC) that includes an amplifier and differential output stage.

Hysteresis

None

Dynamic range (100 Hz BW)

typ. 100 dB (±4g)

Noise (10 to 1000 Hz)

typ. 7 $\mu\text{g}_{\text{rms}}/\sqrt{\text{Hz}}$

Frequency response

0 - 600 Hz

Measuring range

±4 g

Orientation

Horizontal (floor) mounting or vertical (wall mounting)

Self test

Test-pulse

Dimensions

Housing

Aluminum, 120 x 180 x 100 mm

Weight

1.5 kg

Protection degree

IP 65 (splash-proof)

Regulation

Electrical Safety

In compliance with IEC 61010

EMI/RFI

In compliance with EN 61000

Environmental

Shock: 30 g/11 ms half-sine

Heat: -20°C up to +70°C

Humidity: up to 100% RH

Vibration: up to 5 g (operating)

Conformity

CE

Ordering Information (please refer to last page)

Measurement System

MR3003C with internal Velocitymeter

MR3003C with internal Accelerometer

Power supply

External battery pack with integrated AC/DC converter/charger

External AC/DC converter

Mounting Platform

Mounting platform for MR3003C with levelling bubble

GPS timing

GPS receiver and antenna

Carrying case

For MR3003C and battery package

Norm Compliance

Structural damage

- DIN 4150-3 (Germany)
- SN 640312 (Switzerland)
- Circulaire du 23/07/1986 (France)
- Onorm S 9020 (Austria)
- SBR-A (The Netherlands)
- Others available on SCS cloud software

Human comfort

- DIN 4150 -2 (Germany)
- ISO 2631-1 (International)
- ISO 2631-2 (International)
- BS 6472-1 (UK)
- UNI 9614 (Italy)
- SBR-B (The Netherlands)

Syscom Cloud Software (SCS)

The MR3003C can be connected to the Syscom Cloud Software (SCS) in order to simply visualize the data recorded and manage different projects.

The main features of the SCS include:

- plug & play M2M communications
- management by projects
- different access levels (administrator, read/write, view only)
- visualization of events/background monitoring
- comparison with reference standards
- automatic reporting

Please visit scs.syscom-instruments.com for more information.

SCS

scs.syscom-instruments.com

SYSCOM Instruments SA

Rue de l'Industrie 21
1450 Sainte-Croix
SWITZERLAND

T. +41 (0) 24 455 44 11

www.syscom.ch

info@syscom-instruments.com

SCS scs.syscom-instruments.com

Ordering information

Description	Part number	Internal triaxial velocity meter	Internal triaxial accelerometer
MR3003C kits Example: 93106309-A-EU			
Kits MR3003C with: MR3003C recorder - 4GB Memory - WiFi - Ethernet connectivity - Embedded web server for configuration and control - 3 m Ethernet cable - Battery pack with internal AC/DC & cable to MR - External AC/DC converter - Carrying case			
Standard Vel: MR3003C mounting plate - Internal triaxial velocity sensor MS2003+ - horizontal mounting	93106309	x	
Standard Acc: MR3003C mounting plate - Internal triaxial accelerometer MS2008+ - horizontal mounting	93106327		x
Standard Ext Vel: Compatibility with external velocity sensor MS2003+	93106310		
Standard Ext Acc: Compatibility with external accelerometer MS2008+	93106341		
4G module for Europe, Middle East, Africa and Asia	A		
4G module for North America	B		
4G module for Australia, New Zealand and South America	C		
Without 4G module	X		
Cables to Swiss power grid	CH		
Cables to European power grid	EU		
Cables to US power grid	US		

MR3003C main units Example: MR3003C-2003I-H-A-X			
Main unit with: 4GB Memory - WiFi - Ethernet connectivity - Embedded web server for configuration and control	MR3003C		
External triaxial velocity sensor MS2003+	2003E		
Internal triaxial velocity sensor MS2003+	2003I		
External triaxial acceleration sensor MS2008+	2008E		
Internal triaxial acceleration meter MS2008+	2008I		
Horizontal mounting (only with 2003I)	H		
Vertical mounting (only with 2003I)	V		
Horizontal mounting, ± 4 g (only with 2008I)	H4		
Vertical mounting, ± 4 g (only with 2008I)	V4		
External sensor	EX		
4G module for Europe, Middle East, Africa and Asia	A		
4G module for North America	B		
4G module for Australia, New Zealand and South America	C		
Without 4G module	X		
Compatibility with external kit GPS	G		
No compatibility with external kit GPS	X		